



MIN. 26 GAUGE METAL DUCTWORK IN OR ABOVE GARAGE AREA

5/8" FIRE RATED SHEET ROCK ON CEILING IN GARAGE AREA OR OTHER FIRE RETARDANT METHOD AS APPROVED BY LOCAL BUILDING CODES

IF EGRESS WINDOW IS LESS THAN 44" FROM GRADE, MINIMUM EGRESS AREA IS 5.0 SQ. FT.

IF EGRESS WINDOW IS GREATER THAN OR EQUAL TO 44" ABOVE GRADE, MINIMUM EGRESS AREA IS 5.1 SQ. FT.

DOOR FROM GARAGE AREA MUST BE ONE OF THE FOLLOWING:

- STEEL DOOR WITH HONEYCOMB FIRE RETARDANT MATERIAL
- 20 MINUTE FIRE RATED DOOR
- SOLID CORE DOOR

BUILDER TO VERIFY ALL DIMENSIONS AND CONDITIONS PRIOR TO STARTING CONSTRUCTION

<b>TIDWELL DESIGN</b>			
6641 MOBLEY DRIVE, TRUSSVILLE AL 35713 (205) 681-1229			
SCALE: 1/4" = 1' 0"	APPROVED:	DATE: 6/15/09	DRAWN BY: TRAVIS TIDWELL
<b>Floor Plan</b>			DRAWING NUMBER: 09IND016
Mark Ward			